



| REV. | LTR | DATE | UPDATE DESCRIPTION | REMARK | SIGN | APPROVER |
|------|-----|------|--------------------|--------|------|----------|
| △ | | | | | | |


TOP CONN SIDE




TOP LIMIT




TOP PAD




BOTTOM CONN. SIDE





BOTTOM LIMIT



BOTTOM PAD



| | | | | | | | | | | | | | | | |
|---|-----|---|---|---|---|-------|-----------------------|--------|--|--------|--------|--------|-------|-----------|------------------------|
| MATERIAL(SPEC) | | | | | | | QUANTITY/SET 1 PC. | | <div> ASUSTek COMPUTER INC.</div> | | | | | | |
| FINISH | | | | | | | SCALE 1/1 | | | | | | | | |
| SELECT V | | | | | | | UNIT | | DESCRIPTION | | | | | | |
| DIM | TOL | A | B | C | D | EXTRA | M/M | | | | | | | | |
| ~8 | | | | | | | ± 0.03 | ± 0.05 | | | ± 0.10 | ± 0.20 | SHEET | MODEL NO. | DRAWIN NO. PART NO. |
| 8~25 | | | | | | | ± 0.05 | ± 0.08 | | | ± 0.20 | ± 0.30 | | | |
| 25~80 | | | | | | | ± 0.08 | ± 0.12 | | | ± 0.30 | ± 0.40 | | | |
| 80~250 | | | | | | | ± 0.12 | ± 0.20 | | | ± 0.40 | ± 0.50 | | | |
| 250~ | | | | | | | ± 0.20 | ± 0.30 | ± 0.50 | ± 0.60 | | | | | |
| D | | | | | | | C | | B | | A | | | | |
|  | | | | | | | DESIGNED | | APPROVED | | | | | | |